FreshWater® Salt System Ready



FiberCor® High-Density Insulation



Exterior Lighting

HOT SPOT® COLLECTION

PACE





PeopleSeatingJetsVoltage5 SeatsLounge24 Jets115 V or 230 V

Size

6'10" x 6'10" x 33" | 208 cm x 208 cm x 84 cm

Water Care

FreshWater® Salt System Ready



HOT SPOT® COLLECTION

PACF





SHELL COLORS*









Alpine

Pearl

Tuscan Sun

CABINET COLORS*







Almond

Havana Storm

COVER COLORS







Black

Chestnut

LEGENDARY MASSAGE

24 Personalized-Control Jets

- 3 XL Directional Hydromassage jets
- 2 Directional Hydromassage jets
- 2 Rotary Hydromassage jets
- · 17 Directional Precision® jets

EASY WATER CARE

Cover

Water Care System FreshWater® Salt System Ready

Filtration System 30 sq. ft., top loading

LEADING ENERGY EFFICIENCY

Jet Pump Wavemaster® 6200; Two-speed, 1.5 HP Continuous Duty,

WeatherPro™ 4" Tapered Custom-Fit with Hinge Seal

3.2 HP Breakdown Torque

Circulation Pump SilentFlo® 5000 Quiet Continuous Filtration No-Fault® 1,000 W / 115 V or 4,000 W / 230 V Heater Insulation FiberCor® Insulation; Certified to California Energy Commission (CEC) and APSP 14 energy efficiency standards for portable spas SIZE

Dimensions 6'10" x 6'10" x 33" / 208 cm x 208 cm x 84 cm

CAPACITY

Seating Capacity 5 seats

Water Capacity 300 gallons / 1,135 liters

Weight 775 lbs. / 350 kg dry; 4,150 lbs. / 1,880 kg filled**

ADDITIONAL FEATURES

Smart Spa

Hot Spring Spas App Powered by the Connected Spa Kit

Technology*

SmartJet™ System Included

Water Feature Included

Cover Lifters* CoverCradle®, CoverCradle II, Lift 'n Glide®, or UpRite® Steps* Hot Spot Collection Step (Almond, Havana, and Storm)

Entertainment Wireless Sound System

Control System IQ 2020® with LCD control panel

115 V / 20 amp, *60 Hz (Includes GFCI protected power cord)

or 115 V / 30 amp* or 230 V / 50 amp,* 60 Hz

Interior: 10 multi-color LED points of light Exterior: 4 multi-color LED points of light

*Optional Accessories

Lighting System

^{*}Actual colors and products may vary from print representation. See dealer to verify.

^{**}Includes water and 7 adults weighing 175 lbs. each.

^{*}Requires a dedicated circuit supplied to the unit at all times. Electrical requirements will vary outside the U.S. ◆G.F.C.I. protected sub-panel required in 30 amp conversion or 220 V mode. Export models available in 230 V, 50 Hz, 1,000 W heater.